

DRV3 Lite Digital Leakage Receiver & **DSG1 Lite** Digital Signal Generator

Description about the product:

- Cost-effective dual-band leakage meter and signal generator
- Advanced in-home shielding integrity testing (pressure test /system test)
- Frequency-agile in the mid-band (118 to 140 MHz) and LTE-band (600 to 860 MHz)
- Advanced in-home shielding integrity testing
- Audible squelch increases as you move closer to the leakage event
- Real-time RF level display of dual frequencies in split screen
- Bluetooth connectivity to third-party devices (cellular phone, tablets)



The **DRV3 Lite** is a digital leakage receiver designed to operate in all-digital and hybrid cable networks. It operates as a portable find-and-fix meter for the installation or service technicians.

The **DSG1 Lite** dual-band digital signal generator inserts either a low or a high-level signal at the drop cable in order to locate the smallest “hard-to-find” sources of leaks.

SPECIFICATIONS

DSG1 Lite	
DETAILS	
Modulator type	Dual-band digital signal modulator
Output type	Single "F" 75 Ω female connector
Frequency output 1 of 2	Fixed at 126 MHz (mid-band)
Frequency output 2 of 2	Fixed at 612 MHz (LTE-band)
Frequency stability	± 5 KHz
Modulated signal	32 Hz AM tag
Output level from each RF output	High: 50 ± 2 dBmV at 126 MHz / 50 ± 2 dBmV at 612 MHz Low: 30 ± 2 dBmV at 126 MHz / 30 ± 2 dBmV at 612 MHz
Transmission status display	Through an illuminated power button
Power adapter	+12 VDC 1.2 A max
Battery	Pack of 2 rechargeable 7.2 VDC lithium-ion batteries of 2000 mAh ~ 0.3 A
AC Battery Charger	Input 100-240 VAC ~ 50 -60 Hz 0.7A Output: +12 VDC 1.66 A Transient overvoltage II Rated pollution degree 2
Main supply voltage fluctuations	Up to $\pm 10\%$ of the nominal voltage
Operation Time	10 hrs. Continuous on battery power
Operating temperature*	-20°C to $+40^{\circ}\text{C}$ (-4°F to $+104^{\circ}\text{C}$)
Charging temperature*	0°C to 45°C (32°F to 110°C)
Battery charge time	2.25 hrs. for full charge
Storage temperature	-20°C to $+45^{\circ}\text{C}$ (-4°F to $+113^{\circ}\text{C}$)
Maximum relative humidity	80% for temperatures up to 31°C (88°F) decreasing linearly to 50% relative humidity at 40°C (104°F)
Dimensions	4 cm x 12 cm x 13 cm / 1.5" x 4.7" x 5.1" [H x W x D]
Weight	500 g / 17 oz
Recommended use	Indoor use or outdoor use without exposure to direct sunshine or a wet location

* Specifications subject to change without prior notice.

DETAILS	
Detector type	Dual-band digital receiver/demodulator
Channel tuning	Configurable via USB port and/or Bluetooth
Frequency range	Agile from 118 to 140 MHz (mid-band)
Frequency range	Agile from 600 to 860 MHz (LTE-band)
Tuning resolution	100 Hz
Level range	2 to 4,000 $\mu\text{V}/\text{m}$ @ 3 meters (mid-band) 5 to 4,000 $\mu\text{V}/\text{m}$ @ 3 meters (LTE-band)
Measurement units	$\mu\text{V}/\text{m}$ and $\text{dB}\mu\text{V}/\text{m}$
Level accuracy	± 1.5 dB (mid-band) ± 2.5 dB (LTE-band)
Communication port	USB serial port and Bluetooth
Adjustable audible tone	Yes, varies with leak intensity. Can be muted
System tag	AM modulation 20-110 Hz DSB-SC modulation 3480-7000 Hz Video NTSC (mid-band only)
Level scale display	Single scale from 0 to 4,000 $\mu\text{V}/\text{m}$
Operation Time	6 hrs. continuous on battery power
Operating temperature*	-20°C to +40°C (-4°F to +104°F)
Charging temperature*	0°C to 45°C (32°F to 110°F)
Battery charge time	2.25 hrs. for full charge
Storage temperature	-20°C to +45°C (-4°F to +113°F)
Maximum relative humidity	80% for temperatures up to 31°C (88°F) decreasing linearly to 50% relative humidity at 40°C (104°F)
Dimensions	17 cm x 8 cm x 6.7 cm / 6.7" x 3.1" x 1.6" [H x W x D]
Weight	450 g / 16 oz

* Specifications subject to change without prior notice.

CPAT Flex Inc.
8566 Ave de l'Esplanade
Montréal, QC H2P 2R8
www.cpatflex.com
E: sales@cpatflex.com

© 2024 CPATFLEX. All Rights Reserved
The information contained in this document is accurate. However, we reserve the right to change any contents at any time without notice. We accept no responsibility for any errors or omissions. In case of discrepancy, the web version takes precedence over any printed literature.